# **SAFETY DATA SHEET of:**



**Solwax** 

Revision date: Thursday, November 24, 2022

S113.040

# SECTION 1: Identification of the substance/mixture and of the company/undertaking:

# 1.1 Product identifier:

# Solwax

UFI: /

1.2 Relevant identified uses of the substance or mixture and uses advised against:

/

Concentration in use: /

## 1.3 Details of the supplier of the safety data sheet:

#### MONDO SPECHIM S.A.

Chaussée de Tirlemont 75A

5030 Gembloux

Phone: 081830083 - E-mail: mondo-spechim@bechems.eu - Website: https://www.mondo-spechim.eu/

## 1.4 Emergency telephone number:

+32 70 245 245

# SECTION 2: Hazards identification:

#### 2.1 Classification of the substance or mixture:

Classification of the substance or mixture in accordance with regulation (EU) 1272/2008

H319 Eye Irrit. 2

## 2.2 Label elements:

**Pictograms** 



#### Signal word

Warning

#### Hazard statements

H319 Eye Irrit. 2: Causes serious eye irritation.

Precautionary statements

**P264:** Wash hands thoroughly after handling.

**P280:** Wear protective gloves, protective clothing, eye protection, face protection.

P305+P351+P338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact

lenses, if present and easy to do. Continue rinsing.

**P337+P313:** If eye irritation persists: Get medical advice/attention.

Contains

None

#### 2.3 Other hazards:

None

# SECTION 3: Composition/information on ingredients:

#### 3.2 Mixtures:

Isotridecanol, ethoxylated	≤ 3 %	CAS number:	69011-36-5
		EINECS:	/
		REACH Registration number:	/
		CLP Classification:	H302 Acute tox. 4 H318 Eye Dam. 1
		Additional data:	H318 >10% ; ATE(H302) = 500mg/kg
2-(2-butoxyethoxy)ethanol	≤ 3 %	CAS number:	112-34-5
		EINECS:	203-961-6
		REACH Registration number:	01-2119475104-44
		CLP Classification:	H319 Eye Irrit. 2

For the full text of the H phrases mentioned in this section, see section 16.

## SECTION 4: First aid measures:

## 4.1 Description of first aid measures:

Always ask medical advice as soon as possible should serious or continuous disturbances occur.

**Skin contact:** Remove contaminated clothing, rinse skin with plenty of water, if necessary seek

medical attention.

**Eye contact:** Thoroughly rinse with water (contact lenses to be removed if this is easily done)

then take to physician.

**Ingestion:** Rinse mouth, do not induce vomiting, take to hospital immediately.

Inhalation: Let sit upright, fresh air, rest and take to hospital.

#### 4.2 Most important symptoms and effects, both acute and delayed:

Skin contact: None
Eye contact: Redness

Ingestion: Diarrhoea, headache, abdominal cramps, sleepiness, vomiting

Inhalation: None

#### 4.3 Indication of any immediate medical attention and special treatment needed:

None

# SECTION 5: Firefighting measures:

#### 5.1 Extinguishing media:

CO2, foam, powder, sprayed water

#### 5.2 Special hazards arising from the substance or mixture:

None

#### 5.3 Advice for firefighters:

Extinguishing agents to be avoided: None

# SECTION 6: Accidental release measures:

#### 6.1 Personal precautions, protective equipment and emergency procedures:

Do not walk into or touch spilled substances and avoid inhalation of fumes, smoke, dusts and vapours by staying up wind. Remove any contaminated clothing and used contaminated protective equipment and dispose of it safely.

#### 6.2 Environmental precautions:

Do not allow to flow into sewers or open water.

#### 6.3 Methods and material for containment and cleaning up:

Contain released substance, store into suitable containers. If possible, remove by using absorbent material.

#### 6.4 Reference to other sections:

For further information, check sections 8 & 13.

# SECTION 7: Handling and storage:

#### 7.1 Precautions for safe handling:

Handle with care to avoid spillage.

## 7.2 Conditions for safe storage, including any incompatibilities:

Keep in a sealed container in a closed, frost-free, ventilated room.

#### 7.3 Specific end use(s):

/

# SECTION 8: Exposure controls/personal protection:

## 8.1 Control parameters:

Listing of the hazardous ingredients in section 3, of which the workplace exposure limit values are known

2-(2-butoxyethoxy)ethanol 50 mg/m³ (8h)

## 8.2 Exposure controls:

1.1.1.2	De la	
Inhalation protection:	Respiratory protection is not required. Use ABEK type gas masks in case of irritating exposure. If necessary, use with sufficient exhaust ventilation.	
Skin protection:	Handling with nitril-gloves (EN 374). Breakthrough time: >480' Material thickness: 0,35 mm. Thoroughly check gloves before use. Take of the gloves properly without touching the outside with your bare hands. The manufacturer of the protective gloves has to be consulted about the suitability for a specific work station. Wash and dry your hands.	
Eye protection:	Keep an eye-rinse bottle within reach. Tight-fitting safety goggles. Wear a face shield and protective suit in case of exceptional processing problems.	
Other protection:	Wear impermeable clothing. The type of protective equipment depends on the concentration and amount of hazardous substances at the work station in question.	
Environmental controls:	Comply with applicable environmental regulations limiting discharge to air, water and soil. Protect the environment by applying appropriate control measures to prevent or limit emissions. For further information, check sections 6 and 13.	
Engineering controls:	The level of protection and types of controls necessary will vary depending upon potential exposure conditions. Adequate ventilation should be provided so that exposure limits are not exceeded. For further information, check section 7.	

# SECTION 9: Physical and chemical properties:

## 9.1 Information on basic physical and chemical properties:

Appearance/20°C: Liquid

Colour: white

Odour: characteristic

Melting point/melting range: 0 °C

Boiling point/Boiling range:  $100 \, ^{\circ}\text{C} - 280 \, ^{\circ}\text{C}$ Flammability (solid, gas): Not applicable

Lower flammability or explosive limit, (Vol

%):

Upper flammability or explosive limit, (Vol /

%):

Flash point: /
Auto-ignition temperature: /
Decomposition temperature: /
pH: 7.8
pH 1% diluted in water: /

Kinematic viscosity, 40°C: 1 mm²/s

Solubility in water: Not soluble

Partition coefficient: n-octanol/water: Not applicable

Vapour pressure/20°C,: 2,332 Pa

Relative density, 20°C: 1.0160 kg/l
Vapour density: Not applicable

Particle characteristics:

#### 9.2 Other information:

**Dynamic viscosity, 20°C:** 1 mPa.s

Sustained combustion test:

Evaporation rate (n-BuAc = 1): 0.300

Volatile organic component (VOC): 0.28 %

Volatile organic component (VOC): 27.124 g/l

# SECTION 10: Stability and reactivity:

## 10.1 Reactivity:

Stable under normal conditions.

## 10.2 Chemical stability:

Extremely high or low temperatures.

## 10.3 Possibility of hazardous reactions:

None

## 10.4 Conditions to avoid:

Protect from sunlight and do not expose to temperatures exceeding + 50°C.

## 10.5 Incompatible materials:

None

## 10.6 Hazardous decomposition products:

Under recommended usage conditions, hazardous decomposition products are not expected.

# **SECTION 11: Toxicological information:**

## 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008:

## a) acute toxicity:

Not classified according to the CLP calculation method

Calculated acute toxicity, ATE oral: > 2,000 mg/kg
Calculated acute toxicity, ATE dermal: > 2,000 mg/kg

Isotridecanol, ethoxylated	LD50 oral, rat:	500 mg/kg
	LD50 dermal, rabbit:	≥ 5,000 mg/kg
	LC50, Inhalation, rat, 4h:	≥ 50 mg/l

2-(2-butoxyethoxy)ethanol	LD50 oral, rat:	3,305 mg/kg
	LD50 dermal, rabbit:	2,764 mg/kg
	LC50, Inhalation, rat, 4h:	≥ 50 mg/l

## b) skin corrosion/irritation:

Not classified according to the CLP calculation method

## c) serious eye damage/irritation:

H319 Eye Irrit. 2: Causes serious eye irritation.

#### d) respiratory or skin sensitisation:

Not classified according to the CLP calculation method

## e) germ cell mutagenicity:

Not classified according to the CLP calculation method

#### f) carcinogenicity:

Not classified according to the CLP calculation method

## g) reproductive toxicity:

Not classified according to the CLP calculation method

## h) STOT-single exposure:

Not classified according to the CLP calculation method

## i) STOT-repeated exposure:

Not classified according to the CLP calculation method

## j) aspiration hazard:

Not classified according to the CLP calculation method

#### 11.2 Information on other hazards:

No additional data available

# SECTION 12: Ecological information:

#### 12.1 Toxicity:

2-(2-butoxyethoxy)ethanol	LC50 (Fish):	1300 mg/l, 96h (Lepomis microlophus)
	EC50 (Daphnia):	>100 mg/l, 48h
	EC50 (Algae):	ErC50 > 100 mg/l
	EC50 (soil microorganisms):	255 mg/l

## 12.2 Persistence and degradability:

The surfactants contained in this preparation comply with the biodegradability criteria as laid down in Regulation (EC) No.648/2004 on detergents.

## 12.3 Bioaccumulative potential:

No additional data available

#### 12.4 Mobility in soil:

Water hazard class, WGK (AwSV): 1

Solubility in water: Not soluble

#### 12.5 Results of PBT and vPvB assessment:

No additional data available

#### 12.6 Endocrine disrupting properties:

No additional data available

#### 12.7 Other adverse effects:

No additional data available

# SECTION 13: Disposal considerations:

#### 13.1 Waste treatment methods:

The product may be discharged in the indicated percentages of utillization, provided it is neutralised to pH 7. Possible restrictive regulations by local authority should always be adhered to.

# **SECTION 14: Transport information:**

#### 14.1 UN number or ID number:

Not applicable

## 14.2 UN proper shipping name:

ADR, IMDG, ICAO/IATA not applicable

#### 14.3 Transport hazard class(es):

Class(es): Not applicable Identification number of the hazard: Not applicable

## 14.4 Packing group:

Not applicable

#### 14.5 Environmental hazards:

Not dangerous to the environment

## 14.6 Special precautions for user:

Hazard characteristics: Not applicable

Additional guidance: Not applicable

## 14.7 Maritime transport in bulk according to IMO instruments:

Not applicable

# SECTION 15: Regulatory information:

#### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture:

Water hazard class, WGK (AwSV): 1

Volatile organic component (VOC): 0.275 %
Volatile organic component (VOC): 27.124 q/l

Composition by regulation (EC) 648/2004: Nonionic surfactants < 5%, Anionic surfactants < 5%, Perfumes

#### 15.2 Chemical Safety Assessment:

No data available

# **SECTION 16: Other information:**

## Legend to abbreviations used in the safety data sheet:

ADR: The European Agreement concerning the International Carriage of Dangerous

Goods by Road

ATE: Acute Toxicity Estimate
BCF: Bioconcentration factor
CAS: Chemical Abstracts Service

**CLP:** Classification, Labelling and Packaging of chemicals

**EINECS:** European INventory of Existing commercial Chemical Substances

LC50: median Lethal Concentration for 50% of subjects

**LD50:** median Lethal Dose for 50% of subjects

Nr.: Number

PTB: Persistent, Toxic, Bioaccumulative
STOT: Specific Target Organ Toxicity
UFI: Unique Formula Identifier

vPvB: very Persistent and very Bioaccumulative substances

WGK: Water hazard class

**WGK 1:** Slightly hazardous for water

WGK 2: Hazardous for water

WGK 3: Extremely hazardous for water

#### Legend to the H Phrases used in the safety data sheet

H302 Acute tox. 4: Harmful if swallowed. H318 Eye Dam. 1: Causes serious eye damage. H319 Eye Irrit. 2: Causes serious eye irritation.

#### **CLP Calculation method**

Calculation method

## Reason of revision, changes of following items

None

#### SDS reference number

ECM-107169,00

This safety information sheet has been compiled in accordance with annex II/A of the regulation (EU) No 2020/878. Classification has been calculated in accordance with European regulation 1272/2008 with their respective amendments. It has been compiled with the utmost care. We cannot, however, accept responsibility for damage, of any kind, that may be caused by using these data or the product concerned. To use this preparation for an experiment or a new application, the user must carry out a material suitability and safety study himself.